Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name	e or trade mark:	Bettleuchten				
Supplier's addre						
Model identifie						
Type of light so						
Lighting technol		LED	Non-directional or directional:	DLS		
Light source cap-type		SMD LED				
(or other electric interface)						
Mains or non-m	ains:	NMLS	Connected light source (CLS):	Nein		
Colour-tuneable	e light source:	Nein	Envelope:	-		
High luminance	light source:	Nein				
Anti-glare shield	d:	Ja	Dimmable:	No		
Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		2	Energy efficiency class	G		
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		90 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 500		
On-mode power (P _{on}), expressed in W		3,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,50		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	83		
Outer	Height	519	Spectral power	See image		
dimensions	Width	52	distribution in the	in last page		
without	Depth	21				

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity	0,300			
		coordinates (x and y)	0,320			
Parameters for directional light sources:						
Peak luminous intensity (cd)	24	Beam angle in	135			
		degrees, or the				
		range of beam				
		angles that can be				
		set				
Parameters for LED and OLED light sources:						
R9 colour rendering index value	25	Survival factor	0,80			
the lumen maintenance factor	0,96					

(a)'-': not applicable; (b)'-': not applicable;